

ARTICLE NAME:

NUBUCKRAW MATERIAL: **BULL - EUROPE**AVERAGE SIZE: **5.00 m2**THICKNESS: **ca. 1.4 mm - 1.6 mm**

Test	Test method	Result
1. Colour fastness to rubbing: Nr. 50 dry rubs Nr. 20 wet rubs Nr. 20 alkaline ph 8	DIN 53339 / IUF 450 / ISO 11640 DIN 53339 / IUF 450 / ISO 11640 DIN 53339 / IUF 450 / ISO 11640	≥ 3 blue scale ≥ 3 blue scale ≥ 3 blue scale
2. Tear strength	IUP 8 UNI EN ISO 3377 - 2 DIN 53329	≥ 40 N
3. Light resistance (xenon test)	IUF 402 UNI 3377 - 2 ISO 105 - B06	≥ 3 blue scale
4. Fire resistance	UNI EN ISO 1021-1/2 BS 5852 2006 California T.B. 117	pass pass pass

All our leathers comply with the strict regulations and EU Directives covering the use and presence of PCP, CFC, Chromo VI, Dimethylformate (DMF) and Azo dyestuffs during the tanning process. Due to the natural properties of leather colour variations between one dye lot and another may occur. This technical specification sheet replaces any copies in your possession. The values indicated in this sheet refer to the leather at the time of supply. Once the leather has been processed, cut, marked we can no longer guarantee the same values.

A.W. Leder B.V.
Cartografenweg 20
5141 MT Waalwijk,
The Netherlands

Phone +31-(0)416-342 838
Fax +31-(0)416-339 836
e-mail: info@awleder.nl
www.awleder.nl